

APPLICATOR PARTS LIST

TYPE LENGTHWISE AMPLIVAR SPLICE PIGTAIL

SPECIAL FLAT ON CRIMPER & ANVIL
 AMP INCORPORATED HARRISBURG, PENNA. **SHIFTED**

NO.	DESCRIPTION	REQ.	PART NO.
1	WIRE CRIMPER, 125 FLAT	1	455713-3
2	INS. CRIMPER		
3	ANVIL, 125 FLAT	1	455714-3
4	ANVIL SPACER		
5	SHEAR BLADE	1	693012-1
6	REAR SHEAR PLATE	1	465891-1
7	SHEAR BLADE SPACER		
8	FRONT SHEAR PLATE		
9	REAR ANVIL SPACER PLT.		
10	FRONT ANVIL SPACER PLT.		
11	TOOL SPACER		
12	CRIMP SPACER		
13	FRONT STRIP GUIDE	1	691311-8
14	REAR STRIP GUIDE	1	691311-9
15	RAM	1	471167
16	TOOL HOLDER	1	689633-2
17	REAR CRIMP MOUNT & BLADE MT.	1	465755-2
18	SCREW, SOC. HD. CAP	1	3-21000-6
19	APPLICATOR MOUNT ASSY.	1	471707-4
20	BASE PLATE		
21	BASE BLOCK		
22	STRIP GUIDE PLATE		
23	ANVIL HOLDER		
24	AUX. ANVIL HOLDER		
25	STRIPPER - GUARD	1	389072-3
26	STRIPPER MOUNT		
27	RETAINER PLATE		
28	STRIPPER MOUNT BRACKET		
29	STRIPPER BUSHING		
30	STOCK DRAG	1	376666
31	STOCK DRAG HANDLE		
32	STOCK DRAG STUD REAR	1	354045-7
33	STOCK DRAG SPRING REAR	1	1-23847-1
34	STOCK DRAG ADJ. SCREW	2	372997
35	FEED FINGER HOLDER		
36	FEED FINGER	1	452817-1
37	FEED FINGER TIP		
38	FEED FINGER SPACER		
39	BASE CASTING	1	570238
40	GUARD (TOP)		
41	GUARD (BOTTOM)		

NO.	DESCRIPTION	REQ.	PART NO.
42	SCREW, SOC. HD. CAP	2	811651-5
43	WASHER, LOCK	2	21057-4
44	STRIP HOLD DOWN	1	810640-1
45			
46	GUARD ASSY	1	460182-4
47			
48			
49			
50	DRAG BUSHING FRONT	1	452836-1
51	DRAG SCREW FRONT	1	452837-1
52	DRAG SPRING FRONT	1	370572
53			
54	ELBOW		22317-3
55	ELBOW	1	22317-3
56	TUBE	1	689446-2
57	SCREW, SOC. HD. CAP	1	21001-4
58			
59	WASHER, LOCK	1	21024-6
60			
61	LUBRICATOR ASSY.	1	465184-2
62	SYNTHETIC OIL	1	22014-1
63	AIR BLAST ASSY.	1	455350-2
64	MECH. FEED		692140-2
65	TENSION ADJ. PLATE	1	374999
MISCELLANEOUS			
66	TOOL SPACER (FOR SET-UP ONLY)		693619-1
67	NOTE. PLACE ITEM 66 BETWEEN CRIMP		
68	HOLDER ITEM 17 & ALIGN GA.		
69			
70			
71			
72			

125 CRIMPING DATA

TO APPLY TERMINAL U FLAT

TERMINALS 9 SEEL. 62002-62202

WIRE SIZE	CRIMP HEIGHT

CRIMP WIRE	SIZE	TYPE	FEED
	.180	F	
	BLUNT		.315

INSULATION RANGE WIRE RANGE CMA
7000-12,000

EXPLODED VIEW
A-6000 A-6000-5

REMARKS: SPECIAL .800 FORWARD TOP TOOL MOUNTING FROM TOOL HOLDER (16) OUTWARD ITEMS 17, 5 & 1

■ DENOTES WEARING PARTS RECOMMEND PURCHASE REPLACEMENT

THIS APPLICATOR IS TO BE USED ON
AMP-O-ELECTRIC 1-471273-3

MECH. FEED
ALIGN. GA. 679597-1

REV.	REVISION RECORD	DATE	BY	ECN
01	HARDWARE SHEET WAS 217503	1-23-71	TR	L-8593
A	REV PER ECN	5-30-72	TR	L-9139
B	REV PER ECN	10-2-72	TR	E-71
C	ADDED ITEM 46	12-7-74	TR	R-891
D	DELETE 41 810876-1	7-8-75	TR	R-1203
E	DELETE 54, CHK 55, 56, 10005	9-8-75	TR	R-1297
F	REV PER ECN	11-10-75	TR	R-1372
F	ECN A-395892	9-4-76	TR	-

APPLICATOR NUMBER REV. F 566068-1

SHEET 1 of 1

FOR HARDWARE SEE 7-687500-7